

THE BID DOCUMENTS, CONDITIONS OF CONTRACT, DRAWINGS AND SPECIFICATIONS ARE HEREBY AMENDED, AS FOLLOWS:

Amendment 1
Architectural Specifications

1.1 Add the following specification sections, issued herewith:

- 07 81 16 – Fireproofing
- 08 56 88 – Interior Glazed Systems
- 10 22 19 – Demountable Partitions

1.2 Replace the following sections, issued previously, with revised versions, issued herewith:

- 00 01 10 – Table of Contents
- 00 20 00 – Bid Form
- 01 21 00 – Allowances
- 08 14 16 – Wood Doors
- 08 80 00 – Glazing

Amendment 2
Architectural Drawings

2.1 Replace the following Architectural drawings, issued previously, with revised versions, issued herewith:

- A204 – Ground & Second Floor Plan – Renovation
 - Additional door to be provided in Ex. Mechanical Room
- A205 – Roof Plan
 - Additional door to be provided in Ex. Mechanical Room
- A301 – Building Elevations
 - Additional door to be provided in Ex. Mechanical Room
- A304 – Window & Interior Screen Elevation
 - Skylight details added.
- A601 – Interior Elevations & Door Schedule
 - Additional door to be provided in Ex. Mechanical Room
- A702 – Reflected Ceiling Plan Second Floor
 - Skylight details added.

Amendment 3
Mechanical Addendum

3.1 “Mechanical Addendum M-3”, dated April 23, 2024, by Quasar Consulting Group, is issued herewith.

Amendment 4

Q & A

4.1 Please refer to the following Q&A for responses to Contractor questions:

Questions & Responses:

Question 1:

“Drawing L3 shows an exterior concrete pad at the 2 outdoor classrooms, gazebo, 2 childcare sheds and the precast concrete shed. Please provide the structural details for these pads as nothing is shown.”

Response: Provide 200mm deep concrete slab with 15m @ 300 top and bottom in these locations.

Question 2:

“You have asked for a separate price to replace the existing skylight. Please provide details for this work as nothing has been provided.”

Response: Please refer to architectural details provided per amendment 2.

Question 3:

“There are multiple areas on the drawings where you show fireproofing. No specs have been provided for this work.”

Response: Section provided per amendment 1.

Question 4:

“Would you have any as-built drawings of the existing school? In order to properly price the demolition work for this project more details on the existing structure are required.”

Response: As-built drawings of the existing school are incomplete but are provided herewith for information.

Question 5:

“Stair D has a glass guardrail / balustrade. The glazing type / hardware details do not appear to be defined in the specifications. Please advise.”

Response: Section provided per amendment 1.

Question 6:

“In order to occupy the new addition will those zones of the sprinkler system need to be operational in order to achieve occupancy.”

Response: Yes.

Question 7:

“During the site visit we noticed that the school buses use the existing parking area and driveway loop to offload and load the kids. This parking area will be the main entrance for all construction equipment and vehicles involved with the project. This will include personal vehicles, cranes, concrete trucks, concrete pumps, tractor trailers etc. This space will be a high traffic area for construction activity and will be a major safety issue for both the school board and contractors. Would you allow the GC to relocate the existing portables somewhere on the school property and complete the new parking area and school bus lane in the Summer of 2024. This would allow the staff to park in the new parking area and the buses to use the new drop off and pick up lane for the duration of the project.”

Response: Unfortunately, construction of the new parking and school bus lanes cannot be completed in the Summer of 2024. Tree and vegetation removal in the area where the new bus loop is to connect to First Avenue can only begin in October due to natural heritage concerns. There are also concerns that one of the existing portables may not be able to be moved without destroying it.

Question 8:

“Details 15-17/A610 refer to a “300mm long 15M dowel through steel angle bracket” for the wood bench bracket supports. What is the purpose of this dowel? Is the dowel welded to the bracket? What if the dowel interferes with the stud spacing? Please advise.”

Response: Dowel is not required at bench brackets in stud walls.

Question 9:

“Please confirm which set of drawings correctly portray the amount of concrete barrier curb? Architectural Dwg A102 or Civil Drawings SG-1 and SG-2.”

Response: Refer to civil drawings for extent of barrier curbs. Refer to architectural drawings for locations of barrier curb cuts.

Question 10:

“Addendum 04 received, thank you. We are being flooded with calls that a 96-page addendum is not manageable a week before closing. The state of the market currently and time of year makes competitive bidding more difficult: we recommend extending closing AGAIN to Tues. May 7th, and limiting further addenda - thank you.”

Response: Tender extended per Addendum 5. There are no plans to extend further.

Question 11:

“Drawing A601: ‘Childcare’ Door & Frame Schedule’ is indicating that various wood doors are to have a PLAM finish, while the specification 08 14 16 indicates the finish for wood doors to be a “minimum 0.8mm birch veneer finished in accordance with Section 09 91 00”. Upon review of section 09 91 00 as indicated, neither ‘wood veneer’ nor

'plam' is mentioned for door finishes. Can you please clarify which facing should be used on the wood doors, and if it is birch veneer throughout, please provide the specifics of the veneer required, specifically the cut and match required.”

Response: Wood doors to have a PLAM finish. Revised section attached per Amendment 1.

Question 12:

“Spec section 08 70 00: please provide the hardware schedule as noted as being amended to this spec section and as listed as being referred to throughout the Door & Frame Schedules on drawing A601. It is known that the finish door hardware is to be included in the “overall” Base Bid Cash Allowance, but some instances of doors/ frames preparations for the associated hardware rely on the hardware information. Please advise.”

Response: A hardware schedule is not currently available. The specific instances mentioned above will be addressed at that time.

Amendment 5

Handling and Disposal of Contaminated Soils

5.1 Costs for the handling, or handling and disposal, of contaminated soil are to be paid through the cash allowance. The bid form has been revised to request Unit rates at various quantities for the excavation, handling and disposal of contaminated soils exceeding table 1, and table 2 or 3. These unit rates will be used to draw from the cash allowance on an as needed basis as directed by the testing and inspection company.

END OF ADDENDUM 6

1 General

1.1 **SECTION INCLUDES**

- .1 Labour, Products, equipment and services necessary for spray applied fireproofing work in accordance with the Contract Documents.

1.2 **REFERENCES**

- .1 CAN/ULC S101, Standard Methods of Fire Endurance Test of Building Construction and Materials.
- .2 CAN/ULC S102, Standard Method of Test for Surface Burning Characteristics of Building Materials and Assemblies.
- .3 Technical Manual 12-A, Standard Practice for the Testing and Inspection of Field Applied Sprayed Fire-Resistive Materials by Association of the Wall and Ceiling Industry (AWCI).
- .4 UL 1479, Standard Method of Fire Tests of Through-Penetrations.

1.3 **DESIGN REQUIREMENTS**

- .1 Design fireproofing for structural members, floor/ceiling assemblies, and floor/roof assemblies as unrestrained unless otherwise specifically noted as restrained on the structural drawings.

1.4 **SUBMITTALS**

- .1 Product data:
- .1 Submit copies of manufacturer's Product data in accordance with the Conditions of the Contract indicating:
- .1 Performance criteria, compliance with appropriate reference standard, characteristics, limitations.
- .2 Product transportation, storage, handling and installation requirements.
- .2 Certification:
- .1 Submit certified documentation for each worker performing Work of this Section, to substantiate 5 years minimum of experience in sprayed fireproofing installation.
- .2 Submit installer's and Product manufacturer's certification verifying compliance with Contract Documents.
- .3 For assemblies not tested and rated in accordance with CAN/ULC S101 and CAN/ULC S102, submit proposals based on related designs using accepted fireproofing design criteria.
- .4 Submit manufacturer's inspection reports and verification/certification that work has been correctly installed.

1.5 **QUALITY ASSURANCE**

- .1 Qualifications: Execute work of this Section by manufacturer-approved, skilled, qualified, and experienced workers, trained in installation of work of this Section.
- .2 Regulatory Requirements: Be responsible for securing approval of materials and installation of work from authority having jurisdiction:
 - .1 Perform work in compliance with ULC or cUL listed designs for the required fire resistance ratings.
 - .2 Submit signed engineering proposals to Authority having Jurisdiction for acceptance if there are no listed designs that match project conditions.
 - .3 Perform tests required by Authorities having Jurisdiction.
- .3 Manufacturer's Site Inspection: Manufacturer's technical representative shall inspect work at suitable intervals during application and at conclusion of work of this Section, to ensure work is correctly installed. Inspection reports shall be submitted with 3 days.

1.6 **SITE CONDITIONS**

- .1 Maintain a 5°C air and substrate temperature for 24 hours before, during, and 24 hours after application in accordance with manufacturer's instructions.
- .2 Ventilate to dry fireproofing. In enclosed areas circulate interior air and exhaust to the exterior.
- .3 Protect adjacent surfaces and equipment around application areas from overspray, marring or damage. Clean, polish or replace materials damaged to acceptance of Consultant.

2 Products

2.1 **MATERIALS**

- .1 All materials under work of this Section, including but not limited to, primers, adhesives, paints, and sealers are to have low VOC content limits.
- .2 Primer: As recommended by spray fireproofing manufacturer.
- .3 Spray fireproofing: CAN/ULC S101, Spray applied, cementitious fireproofing with a minimum density of 240 kg/m³:
 - .1 'Blaze-Shield II' by Cafco Industries Ltd.
 - .2 'Southwest Type 5GP' by A/D Fire Protection Systems Inc.
 - .3 Or approved alternative by Carboline.
- .4 Sealer: As recommended by spray fireproofing manufacturer qualified for use in specified design.

- .5 Metal Lath: Expanded metal lath fabricated from material of weight, configuration, and finish required to comply with fire resistance designs acceptable to Authority having Jurisdiction and fire resistive material manufacturer's written recommendations. Include clips, lathing accessories, corner beads, and other anchorage devices required to attach lath to substrates and to receive sprayed fire-resistive material.
- .6 Water: Clean, free from organic and mineral impurities which would be harmful to application.

2.2 **MIXING**

- .1 Mix Products in accordance with manufacturer's instructions.

3 Execution

3.1 **EXAMINATION**

- .1 Verify condition and dimensions of previously installed Work upon which this Section depends. Report defects to Consultant. Commencement of work of this Section means acceptance of existing conditions.
- .2 Verify that substrates are compatible and have suitable bonding characteristics to receive fireproofing.
- .3 Ensure written confirmation is received from steel fabricators of the specific surface preparation procedures and primers used to ascertain compatibility with work of this Section.
- .4 Ensure that items required to penetrate fireproofing are placed before installation of fireproofing.
- .5 Ensure that ducts, piping, equipments, or other items which would interfere with application of fireproofing are not positioned until fireproofing is completed.

3.2 **PREPARATION**

- .1 Prime substrates where required by ULC or by sprayed fireproofing material manufacturer, unless compatible shop primer has been applied and is in satisfactory condition to receive work.
- .2 Clean surfaces of steel members free of dust, dirt, oil, grease, loose paint, mill scale, rust and other foreign matter in accordance with manufacturers written instructions which would interfere with bond of fireproofing. Steel to receive fireproofing should have no primers or coatings applied to the surface prior to application.

- .3 Install metal lath where required to comply with fire resistance ratings and fireproofing manufacturer's written recommendations for conditions of exposure and intended use. Securely attach lath to substrate in position required for support and reinforcement of fire-resistive material. Use anchorage devices of type recommended in writing by sprayed fire-resistive material manufacturer. Attach lathing accessories where indicated or required for secure attachment to substrate.
- .4 Coat substrates with bonding adhesive where required to achieve fire resistance rating or as recommended in writing by spray fireproofing manufacturer for material and application indicated.
- .5 Use temporary enclosures to prevent spray from contaminating air beyond application area. Protect adjacent surfaces and equipment from damage by overspray, fall-out, and dusting of fireproofing material. Protect walls, windows, floors and other surfaces around areas to be fireproofed, from marring or damage.

3.3 **APPLICATION**

- .1 Apply fireproofing in separate coats in accordance with the manufacturer's written instructions to total thickness required to achieve fire ratings shown on the Contract Drawings. Comply with accepted ULC or Intertek Testing Services design.
- .2 Maintain continuity of fireproofing without gaps or voids.
- .3 Water tamping: Provide low pressure spray to finished surface of fireproofing to provide dense, medium smooth surface.
- .4 Apply sealer to surfaces of fireproofing in accordance with the manufacturer's instructions after tamping.
- .5 Repair fireproofing damaged by other trades, to acceptance of Consultant.

3.4 **FIELD QUALITY CONTROL**

- .1 Perform field tests as required by Authorities having Jurisdiction. Tests to be carried out as outlined in Technical Manual 12-A by AWCI and UL 1479.

3.5 **CLEANING UP**

- .1 Clean exposed wall, ceiling or other surfaces of fireproofing materials to the acceptance of Consultant.

END OF SECTION

1 General

1.1 **SECTION INCLUDES**

.1 Design, labour, Products, tool, equipment and services necessary for interior glazed system work in accordance with the Contract Documents.

1.2 **REFERENCES**

.1 ASTM A167, Specification for Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet and Strip.

.2 ASTM A276, Specification for Stainless and Heat-Resisting Steel Bars and Shapes.

.3 ASTM C920, Specification for Elastomeric Joint Sealants.

.4 ASTM F738M, Specification for Stainless Steel Metric Bolts, Screws, and Studs.

.5 CAN/CGSB 12.20-M, Structural Design of Glass for Buildings.

.6 CSA-A500, Building Guards.

1.3 **DESIGN REQUIREMENTS**

.1 Design the entire interior glazed system, including framing and supports as required.

.2 Design glass balustrade systems to CSA-A500, CAN/CGSB-12.20-M and CSA-S157/S157.1. Perform stress analysis. Design units to accommodate live, dead, lateral, wind, seismic, handling, transportation, and erection loads.

.3 Prevent deflection and permanent or progressive glazing displacement. Restrict horizontal and vertical mullion deflection to less than $L/175$ (under uniformly distributed positive design wind load), and 10 mm maximum regardless of span.

.4 Design anchorage inserts for installation as part of other Sections of Work. Design anchorage assemblies with a minimum safety factor of 2.0.

.5 Design members to withstand dead load and live loads calculated in accordance with OBC and applicable local regulations, to maximum allowable deflection of $1/360$ of span.

1.4 **SUBMITTALS**

.1 Shop Drawings:

.1 Submit Shop Drawings in accordance with the Conditions of the Contract indicating:

.1 Plans, sections, details, type of extrusions, profiles, thicknesses, seals, finishes, panels, operating components, related flashings, closures, fillers, and end caps, and sealants.

.2 Products and glazing types.

.3 Anchorage inserts, system installation tolerances.

.4 Section and hardware reinforcement, anchorage, assembly fixings.

- .5 Detailing, locations, and allowances for movement, expansion, contraction.
- .2 Samples:
 - .1 Submit two samples of following in accordance with the Conditions of the Contract.
 - .1 250 mm long samples of each type of extrusion and finish.
 - .2 250 x 200 mm samples of glass.
- .3 Reports/Certificates:
 - .1 Submit documentation to substantiate ten years of experience in glazed partition manufacture and installation.
 - .2 Submit written manufacturer's certificate certifying compliance with the specifications.
- .4 Close-out submittals: Submit data for incorporated into the Operations and Maintenance Manual as part of the Conditions of the Contract.

1.5 **QUALITY ASSURANCE**

- .1 Retain a licensed Professional Engineer, registered in Province of Ontario, to perform following services for interior glazed system work:
 - .1 Design of interior glazed systems.
 - .2 Review, stamp, and sign Shop Drawings.
 - .3 Conduct on-Site inspections and prepare and submit inspection reports.

1.6 **DELIVERY, STORAGE, AND HANDLING**

- .1 Handle glazed partition work in accordance with AAMA CW-10.
- .2 Protect surfaces with strippable coating. Do not use adhesive papers or sprayed coatings which bond when exposed to sunlight or weather. Do not remove before final cleaning of building.

1.7 **EXTENDED WARRANTY**

- .1 Submit an extended warranty for interior glazed system work in accordance with General Conditions, except that warranty period is extended to 5 years.
 - .1 Warrant against failure to meet the design criteria and requirements.
 - .2 Coverage: Complete replacement including affected adjacent work.

2 **Products**

2.1 **ACCEPTABLE MANUFACTURER(S) AND SYSTEM(S)**

- .1 Glazed balustrade system (standoffs):
 - .1 Stainless steel standoff fittings with rectangular backplate and six anchor points: 'RS0B20 Glass Rail Standoff Fittings' by C.R. Laurence or approved alternative by Inkan Limited or Richelieu. Provide sizing as required to suit glass sizing and weight.

- .2 Glass mounted handrail: Glass mounted handrail with bracket, fabricated from 38 diameter tubing; 'HRS Newport Series Handrails' by C.R. Laurence or approved alternative by Inkan Limited or Richelieu.
- .3 Finish: Type 316 stainless steel with brushed finish.

2.2 MATERIALS

- .1 General: All materials under work of this Section, including but not limited to, sealants and coatings are to have low VOC content limits.
- .2 Stainless steel shapes: ASTM A276, Type 316. Sizes and shapes as shown.
- .3 Reinforcements and anchors: ASTM A167, Type 316. Size as shown.
- .4 Glass and glazing materials: In accordance with Section 08 80 00.
- .5 Glazing gasket: EPDM roll-in glazing gasket.
- .6 Frame sealant: Type as recommended by the interior glazed system work manufacturer.
- .7 Glazed work sealant: ASTM C920; Single-Component, silicone sealant; 'Spectrem 1' by Tremco or '790 Silicone Building Sealant' by Dow Corning Corporation. Colour as selected by Engineer.
- .8 Joint backing: Closed cell foam polyethylene rod, oversized minimum 30-50% larger than joint width and compatible with joint sealant. Product as recommended by sealant manufacturer.
- .9 Anchors, clips, and angles: Stainless steel.
- .10 Flashings, closures and trim: 1 mm minimum stainless steel sheet to match framing.
- .11 Screws, bolts and other fasteners: ASTM F738M; Stainless Steel Type 316.

2.3 FABRICATION

- .1 Fabricate sections true to detail, free from defects impairing appearance, strength and durability. Fabricate extrusions with sharp, well defined corners.
- .2 Fabricate, fit, and secure framing joints and corners accurately, with flush surfaces, and hairline joints. Apply frame sealant at joints for weatherproof seams.
- .3 Conceal anchors, reinforcement and attachments from view. Fabricate reinforcement in accordance with design requirements.
- .4 Do not expose manufacturer's identification labels on interior glazed system assemblies.
- .5 Fabricate continuous sill flashings with intermediate anchor clips, and joint reinforcing, form to profile shown. Fabricate filler and closure pieces as necessary for a complete and weather tight installation.

- .6 Fabricate interior glazed system work closures and trim from stainless steel sheet.

3 Execution

3.1 **EXAMINATION**

- .1 Verify condition and dimensions of previously installed Work upon which this Section depends. Report defects to Consultant. Commencement of work of this Section means acceptance of existing conditions.

3.2 **INSTALLATION**

- .1 Install interior glazed system work in accordance with reviewed Shop Drawings, manufacturer's written instructions.
- .2 Install work of this Section securely, in correct location, level, square, plumb, at proper elevations, free of warp or twist.
- .3 Install flashings, closures, and trim pieces.
- .4 Install sills in maximum lengths possible. For sills over 1200 mm in length, maintain 3 mm to 6 mm space at each end.
- .5 Refer to Contract Drawings for glazing type locations. Install glazing in accordance with Section 08 80 00.
- .6 Adjust operable parts for correct function.
- .7 Install glass in balustrades properly centred with uniform bite and face and edge clearance, free from twist, warp or other distortion likely to develop stress.
- .8 Remove damaged or unacceptable Products and assemblies from Site and replace to Engineer's acceptance.
- .9 Install glass presence markers, in two cross stripes extending from diagonal corners. Maintain markers until final clean-up.

3.3 **ERECTION TOLERANCES**

- .1 Tolerances: Non-cumulative.
 - .1 Maximum variation from plumb: 1.5 mm/3 m non-cumulative or 12 mm/30 m, whichever is less.
 - .2 Maximum misalignment of two adjoining members abutting in plane: 0.8 mm.
 - .3 Vertical and horizontal positions: +/- 3 mm.
 - .4 Racking of face: 6 mm, nil in elevation.
 - .5 Operable components: Consistent with smooth operation and weatherproof performance.
 - .6 Maximum perimeter sealant joint between interior glazed system and adjacent construction: 12 mm.

3.4 JOINT BACKING AND GLAZED WORK SEALANT

- .1 Prepare substrate surface and mask as recommended by sealant manufacturer.
- .2 Install joint backing and sealant at interior glazed system work and perimeter joints for sound tight installation in accordance with sealant manufacturer's instructions. Tool sealant. Remove excess sealant.

3.5 CLEANING

- .1 Maintain interior glazed system work, inside and outside, in clean condition throughout construction period.
- .2 Remove labels, protective material, and glass presence markers from prefinished surfaces.
- .3 Wash interior glazed system work with solution of mild detergent in warm water, with particular attention to recesses and corners. Wipe surfaces clean and dry.

END OF SECTION

1 General

1.1 **SECTION INCLUDES**

.1 Design, labour, Products, equipment and services necessary for demountable partition work in accordance with the Contract Documents.

1.2 **REFERENCES**

.1 AAMA 611, Voluntary Standards for Anodized Architectural Aluminum.

.2 AAMA CW-10, Care and Handling of Architectural Aluminum from Shop to Site.

.3 ANSI, H35.1M Alloy and Temper Designation Systems for Aluminum (Metric).

.4 ASTM A653/A653M, Specification for Steel Sheet, Zinc-coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvanealed) by the Hot-Dip Process.

.5 ASTM B209M, Specification for Aluminum and Aluminum-Alloy Sheet and Plate.

.6 ASTM B221M, Specification for Aluminum-Alloy Extruded Bars, Rods, Wires, Shapes and Tubes.

.7 ASTM C1396, Specification for Gypsum Board.

.8 ASTM C645, Specification for Non-Load Bearing (Axial) Steel Studs, Runners (Tracks), and Rigid Furring Channels for Screw Application of Gypsum Board.

.9 ASTM E90, Standard Test Method for Laboratory Measurement of Airborne Sound Transmission Loss of Building Partitions and Elements.

.10 ASTM F738M, Specification for Stainless Steel Metric Bolts, Screws, and Studs.

1.3 **DESIGN REQUIREMENTS**

.1 Demountable partition system to be 89 mm wide, with flush joints, system components, door frames, wood doors, glazed openings, and all trim components.

.2 Design partition system to provide an STC of 35 when tested in accordance with ASTM E90.

.3 Design partition system to allow for all panels to be point accessible without affecting adjoining panels.

1.4 **SUBMITTALS**

.1 Product data:

.1 Submit copies of manufacturer's Product data in accordance with the Conditions of the Contract indicating:

.1 Performance criteria, compliance with appropriate reference standard, characteristics, and limitations.

- .2 Product transportation, storage, handling and installation requirements.
- .2 Shop drawings:
 - .1 Submit shop drawings in accordance with the Conditions of the Contract indicating:
 - .1 Location, construction, adjacent construction, elevations, sections, panel sizes, interior structure and/or reinforcement, door and glazing modules, frame details, trim, connection to ceiling grid system, details, anchorages, dimensions, thickness, joints, and finishes.
- .3 Samples:
 - .1 Submit following samples in accordance with the Conditions of the Contract.
 - .1 Two 300 x 300 mm samples of finishes applied to gypsum board.
 - .2 One 300 mm long sample of door frames, glazing framing and trim.
 - .3 One of each component used in the partition system i.e. ceiling fixing device and other component parts.

1.5 **QUALITY ASSURANCE**

- .1 Installers qualifications: Perform work of this Section by a company that has a minimum of five years proven experience in the installation of demountable partition systems of a similar size and nature and that is approved by manufacturer. Submit to Consultant, applicator's current certificate of approval by the material manufacturer as proof of compliance.
- .2 Mock-up:
 - .1 Construct a mock-up of at least 4 panels in location acceptable to Consultant.
 - .2 Arrange for Consultant's review and acceptance, allow 48 hours after acceptance before proceeding with work.
 - .3 Mock-up may remain as part of Work if accepted by Consultant. Remove and dispose of mock-ups which do not form part of Work.
 - .4 Upon acceptance, mock-up shall serve as a minimum standard of quality for the balance of the work of this Section.

1.6 **SITE CONDITIONS**

- .1 Do not begin work of this Section until:
 - .1 Floor and ceiling finishes are complete.
 - .2 Substrate and ambient temperature is above 15°C.
 - .3 Relative humidity is below 80 %.
- .2 Install temporary protection and facilities to maintain Product manufacturer's, and above specification, environmental requirements 48 h before, during, and 48 h after installation.

1.7 **DELIVERY, STORAGE, AND HANDLING**

- .1 Handle aluminum in accordance with AAMA CW-10.

- .2 Protect aluminum surfaces with strippable coating. Do not use adhesive papers or sprayed coatings which bond when exposed to sunlight or weather. Do not remove before final cleaning of building.

2 Products

2.1 **ACCEPTABLE PRODUCT(S) AND MANUFACTURER(S)**

- .1 'Elite Glazing Wall System' by PC350 or approved alternative.

2.2 **MATERIALS**

- .1 Galvanized steel sheet: ASTM A653/A653-M, Z275; cold rolled, galvanized steel sheet.
- .2 Aluminum extrusions: ASTM B221 and ANSI H35.1 AA6063 alloy, T5 temper.
- .3 Aluminum sheet: ASTM B209 and ANSI H35.1 AA1100 aluminum alloy, H14 temper, minimum 3.0 mm thick.
- .4 Top track: ASTM C645; cold rolled channels, formed from galvanized steel sheet, designed to accept snap-on trim from either side of wall.
- .5 Bottom track: ASTM C645; roll formed from galvanized steel sheet, with 38 mm high legs.
- .6 Steel studs and runners: ASTM C645; 'U' shape, roll formed from galvanized steel sheet, 0.6 mm thick minimum, pre-punched openings for system elements, configured to meet panel system requirements, depth as indicated on Contract Drawings.
- .7 Cross locking Channels: ASTM C645; 3350 mm long, roll formed from galvanized steel channels.
- .8 Sliding doors: Standard profile extruded aluminum frame with 6 mm thick glazing, hardware to provide smooth, gentle soft close glide and come with braking mechanism and seal, in size shown on drawings. Door pull handle to be selected by Consultant.
- .9 Glazing frames: Extruded aluminum, complete with snap-on glazing stops and neoprene gaskets for setting glass.
- .10 Glazing: In accordance with Section 08 80 00.
- .11 Finish hardware: In accordance with Section 08 70 00.
- .12 Trim: Aluminum, colour to match frames.
- .13 Fasteners: ASTM F738M; Stainless Steel Type 304.

2.3 **FINISHES**

- .1 Aluminum finish: Clear anodized to AAMA 611 per Aluminum Association Designation System for Aluminum Finishes AA-M12C22A41.

3 Execution

3.1 **EXAMINATION**

- .1 Verify condition and dimensions of previously installed Work upon which this Section depends. Report defects to Consultant. Commencement of work of this Section means acceptance of existing conditions.

3.2 **INSTALLATION**

- .1 Install demountable partition system in accordance with reviewed Shop Drawings and manufacturer's written instructions.
- .2 Install partition system on top of floor finish and accurately fitting to suspended ceiling.
- .3 Erect partitions plumb, square, straight, rigid, and with horizontal lines level. Accurately fit and fasten to abutting surfaces.
- .4 Provide reinforcement and bracing wherever necessary to assure lateral stability.
- .5 Coordinate with mechanical and electrical trades for all services required to be built into partition system.
- .6 Fasten runners to floors, ceiling and abutting vertical surfaces at 600 mm o.c. At ceilings, use fasteners that rigidly support partition without damaging or defacing ceiling panels or grid members. At carpets, use fasteners that rigidly support partition without damaging or defacing carpet.
- .7 Fasten floor track to substrate at both sides of door frames.
- .8 Install continuous light/sound seal at junction between partition system and ceilings, floors, and adjacent abutting surfaces.
- .9 Install studs vertically in floor and ceiling track at 600 mm. Install three cross channels per stud.
- .10 Install panel clips and hang panels on framework taking care to seat all panel clips on cross channels.
- .11 Glaze partition system in accordance with Section 08 80 00.
- .12 Install finish hardware in accordance with Section 08 70 00.
- .13 Install ceiling trims, base moulding, corners, and other trim to provide a complete system.

- .14 The complete installation shall be free of exposed screws or other fasteners, with surfaces free of tool marks, scratches or any other marred surface detrimental to appearance.

3.3 **CLEANING**

- .1 Upon completion of work of this section, remove strippable coatings, clean surfaces, and adjust doors for proper operation.

END OF SECTION

SECTION NO.	TITLE	NO. OF PAGES
<u>DIVISION 00 PROCUREMENT AND CONTRACTING REQUIREMENTS</u>		
00 01 07	Professional Certifications	1
00 01 10	Table of Contents	4
00 10 00	Instructions to Bidders	10
00 20 00	Bid Form	4
00 21 00	Bid Form Appendix A	3
00 30 00	Supplementary Conditions to CCDC2-2020.....	66
<u>DIVISION 01 GENERAL REQUIREMENTS</u>		
01 10 00	Summary of Work.....	1
01 21 00	Allowances	2
01 26 00	Contract Modification Procedures	1
01 29 00	Payment Procedures	2
01 30 00	Administrative Requirements	5
01 32 33	Photographic Documentation.....	1
01 40 00	Quality Requirements	4
01 41 00	Regulatory Requirements	2
01 42 00	References	2
01 50 00	Temporary Facilities and Controls	6
01 51 16	Temporary Fire Control.....	1
01 57 19	Temporary Environmental Controls	5
01 61 00	Common Product Requirements.....	5
01 70 00	Execution Requirements.....	3
01 74 00	Cleaning and Waste Management.....	2
01 77 00	Closeout Procedures	3
01 78 00	Closeout Submittals.....	5
<u>DIVISION 02 EXISTING CONDITIONS</u>		
02 40 00	Demolition and Removals	98
<u>DIVISION 03 CONCRETE</u>		
03 30 53	Cast-in-Place Concrete.....	20
03 41 13	Precast Concrete Hollow Core Planks	8
<u>DIVISION 04 MASONRY</u>		
04 20 00	Concrete and Clay Units Masonry	11
<u>DIVISION 05 METALS</u>		
05 21 19	Structural Steel and Open Wb Steel Joist Framing.....	16
05 31 23	Steel Roof Decking.....	7
05 41 00	Load-Bearing Metal Studs	5
05 50 00	Miscellaneous and Metal Fabrications	6
<u>DIVISION 06 WOOD, PLASTICS AND COMPOSITES</u>		
06 10 00	Rough Carpentry	5
06 20 00	Finish Carpentry & Architectural Woodwork	9

DIVISION 07 THERMAL AND MOISTURE PROTECTION

07 11 00	<i>Damproofing</i>	3
07 13 00	Sheet Waterproofing.....	4
07 16 00	Cementitious Waterproofing	6
07 21 00	Thermal Insulation	3
07 21 19	Sprayed Insulation	4
07 26 00	Vapour Retarders	5
07 40 25	Exterior Soffit System	3
07 42 40	Composite Panels.....	8
07 46 19	Metal Siding.....	6
07 52 00	Modified Bituminous Roofing	10
07 62 00	Flashing and Sheet Metal	3
07 81 16	<i>Fireproofing</i>	
07 85 00	Firestopping and Smoke Seals	7
07 92 00	Sealants	5
07 95 13	Expansion Joint Cover Assemblies.....	4

DIVISION 08 DOORS AND OPENINGS

08 11 13	Metal Doors and Frames	6
08 14 16	Wood Doors	4
08 31 00	Access Panels	2
08 44 00	Aluminum Work	12
08 51 13	Aluminum Windows	8
08 56 88	<i>Interior Glazed Systems</i>	
08 70 00	Finish Hardware.....	5
08 80 00	Glazing	7

DIVISION 09 FINISHES

09 21 16	Gypsum Board.....	11
09 30 00	Tile	6
09 30 27	Detectable/Tactile Tiles	3
09 51 00	Acoustical Ceilings.....	5
09 65 16	Resilient Flooring.....	6
09 67 23	Epoxy Flooring.....	4
09 67 72	Concrete Floor Sealer.....	3
09 68 19	Tile Carpeting	3
09 83 00	Acoustical Panels	4
09 91 00	Painting	9

DIVISION 10 SPECIALTIES

10 22 19	Demountable Partitions	5
10 22 19	<i>Demountable Partitions</i>	5
10 28 13	Washroom Accessories	4
10 44 16	Fire Extinguishers (Refer to Mechanical Specifications) ..	2
10 51 00	Lockers.....	2
10 80 00	Miscellaneous Specialties	23

DIVISION 11 EQUIPMENT

11 66 23 Gymnasium Equipment34

DIVISION 12 FURNISHINGS

12 21 23 Window Coverings.....5

DIVISION 14 CONVEYING SYSTEMS

14 24 23 Holeless Hydraulic Elevator 16

DIVISION 20 COMMON REQUIREMENTS FOR MECHANICAL

See attached Mechanical Table of Contents

DIVISION 21 FIRE SUPPRESSION

See attached Fire Suppression Table of Contents

DIVISION 22 PLUMBING

See attached Mechanical Table of Contents

DIVISION 23 HEATING, VENTING AND AIR CONDITIONING (HVAC)

See attached Mechanical Table of Contents

DIVISION 25 INTEGRATED AUTOMATION

See attached Mechanical Table of Contents

DIVISION 26 ELECTRICAL

See attached Electrical Table of Contents

DIVISION 27 COMMUNICATIONS

See attached Communication Table of Contents

DIVISION 28 ELECTRONIC SAFETY AND SECURITY

See attached Security Table of Contents

DIVISION 31 EARTHWORK

31 00 00 Earthwork9
31 22 19.13 Topsoil & Finish Grading2

DIVISION 32 EXTERIOR IMPROVEMENTS

32 12 16 Asphaltic Concrete Paving5
32 16 13 Concrete Curbs and Pavements9
32 33 00 Site Specialties2
32 92 10 Trees, Shrubs, and Grouncovers6

DIVISION 33 UTILITIES

33 46 13 Foundation Drainage3

APPENDIX

Colour & Materials Schedule..... 16
Geotechnical Investigation Report (Terraprobe) 75
Hydrogeological Report (Terraprobe)..... 109
Phase 2 ESA (Terraprobe)..... 171
Soil Quality Assessment (Terraprobe)24

END OF SECTION

**Tender No.: T-2024-PPS02
BID FORM**

Submitted to: Algonquin & Lakeshore Catholic District School Board
151 Dairy Avenue
Napanee Ontario
K7R 4B2

PROJECT: J.J. O'Neill Catholic Elementary School
Napanee, ON

PROJ. NO.: 22026

ATT: Brad Hurdis, Capital Projects Manager **DATE:** _____

1. Bidder

Name: _____

Address: _____

Email: _____

Fax: _____

2. Bid Price

Having examined the Place of Work and bid documents for J.J. O'Neill Catholic Elementary School, to perform the Work required by the documents as prepared by Salter Pilon Architecture Inc. and consultants including addenda listed herein, inclusive, we hereby offer to enter into a Contract to perform the Work required by the documents for the Stipulated price of:

_____ dollars. (\$ _____)

in Canadian Funds, which price excludes HST.

Prices are free of escalation clauses.

This offer is valid for a period of **sixty (60)** days from close of bidding.

Should either party fail to make payments as they become due under the terms of the Contract, interest at one percent (1 %) per annum above the Bank Rate on such unpaid amounts shall also become due and payable until payment. Such interest shall be compounded on a monthly basis. The Bank Rate means the bank rate established by the Bank of Canada as the minimum rate at which the Bank of Canada makes short term advances to the Chartered Banks.

3. Addenda

The following Addenda have been received. The modifications to the Contract Documents noted therein have been considered and all costs thereto are included in the Bid Price.

- Addendum #Dated
- Addendum #Dated
- Addendum #Dated
- Addendum #Dated
- Addendum #Dated

4. Schedule:

The Contractor hereby declares that they will commence work immediately upon award of Contract and attain Substantial Performance of the Work by _____ (completion date or number of weeks)

5. Cash Allowances:

A Cash Allowance, with a value of \$545,000.00, as outlined in Section 01 21 00 is included as part of the Base Bid Price and shall cover the following (in general):

- .1 Finish Hardware: Supply and Install for wood and HM doors. Supply of finish hardware for aluminum doors – installation by others. Supply of finish hardware for teacher’s and storage closet doors – installation by others.
- .2 Pin mounted cast aluminum signage
- .3 Hydro Utility – supply and install of the primary terminations. Connection at the supply point at street and pad mounted transformer. Utility service connection fees.
.1 Note: The Electrical Contractor shall be responsible for coordinating a servicing agreement and all associated work with the electrical company.
- .4 Testing and Inspection.
- .5 Security Alarm Systems – Supply and install as per Division 26 Sections,
- .6 A/V systems – supply and install in gymnasium.
- .7 Gas meter upgrades by Utility provider.
- .8 Unexpended amounts of Cash Allowances may be reallocated to other work at the sole discretion of the Consultant and Owner.

6. Unit Prices

The Bidder shall perform any additional work that may be required and supply whatever additional articles, materials, or equipment which may be necessary at the unit prices or adjusted unit prices set out below in strict conformance with all terms and conditions of the Contract. The unit price for deductions shall be 90% that for additions.

Trade or Material	Additional Cost	/unit
Rock Removal (machine) – Includes removal & disposal	_____	/m ³
Engineering Fill Granular B Placed	_____	/m ³
Removal of Contaminated Soils (include excavation, haulage, and disposal) exceeding table 1, and in the range of 1-100 tonnes (to be paid by cash allowance).	_____	/tonne
Removal of Contaminated Soils (include excavation, haulage, and disposal) exceeding table 1, and in the range of 101-500 tonnes (to be paid by cash allowance).	_____	/tonne
Removal of Contaminated Soils (include excavation, haulage, and disposal) exceeding table 1, and greater than 500 tonnes (to be paid by cash allowance).	_____	/tonne
Removal of Contaminated Soils (include excavation, haulage, and disposal) exceeding tables 2 or 3, and in the range of 1-100 tonnes (to be paid by cash allowance).	_____	/tonne
Removal of Contaminated Soils (include excavation, haulage, and disposal) exceeding tables 2 or 3, and in the range of 101-500 tonnes (to be paid by cash allowance).	_____	/tonne
Removal of Contaminated Soils (include excavation, haulage, and disposal) exceeding tables 2 or 3, and greater than 500 tonnes (to be paid by cash allowance).	_____	/tonne

7. Bidder's Alternatives

I/We the undersigned propose the following alternatives:

<u>Product Specified</u>	<u>Proposed Substitution</u>	<u>Deduct from Bid Price</u>
1 _____		\$ _____
2 _____		\$ _____
3 _____		\$ _____

(Add extra lines or pages if necessary)

8. Declarations:

We hereby declare that no person, firm, or corporation other than the undersigned has any interest in this Bid or in the proposed Contract for which this Bid is made.

9. Signatures:

Signed and Submitted for and on behalf of:

name of bidder

Seal:

signature

print name and title of person signing

Witness:

signature

signature

print name and title of person signing

print name and title of person signing

Date: _____

Note: this Bid form must be signed in one of the following ways:
For a corporation: minimum of one signing officer. Corporate seal to be affixed.
For a Partnership: two Partners must sign.
For a Sole Proprietorship: The Owner plus one witness must sign.

END

- 1 GENERAL
 - .1 Include all allowances listed below in the Bid Price.
 - .2 Expend Cash Allowances as directed by the Consultant.
 - .3 Each Cash Allowance will be adjusted to actual cost as defined hereunder and Contract Price will be amended accordingly by written order.
 - .4 Progress payments for work and material authorized under Cash Allowances will be made in accordance with GC 5.3 of the Contract.
 - .5 Where costs under a cash allowance exceed amount of allowance, Contractor will be compensated for excess incurred and substantiated plus allowance for overhead and profit as set out in Contract Documents.
 - .6 Include progress payments on accounts of Work authorized under cash allowances in Consultant's monthly certificate for payment.
 - .7 Prepare schedule jointly with Consultant and Contractor to show when items called for under cash allowances must be authorized by Consultant for ordering purposes so that progress of Work will not be delayed.
 - .8 Cash allowances do not include H.S.T.
- 2 MATERIAL ALLOWANCES (SUPPLY ONLY)
 - .1 Material cash allowance shall include and provide payment for:
 - .1 Net cost of material.
 - .2 Applicable duties and taxes.
 - .3 Delivery to the Place of the Work.
 - .2 Include in the Bid Price, in addition to the material cash allowance, costs for the following:
 - .1 Handling at the Place of the Work, including unloading, uncrating, storage and hoisting.
 - .2 Protection from damage by elements or otherwise.
 - .3 Labour for installation and finishing.
 - .4 Other expenses required to complete installation.
 - .5 Overhead and profit.
- 3 ASSEMBLY ALLOWANCES (SUPPLY AND INSTALL)
 - .1 Assembly cash allowance shall include and provide payment for:
 - .1 Net cost of material.
 - .2 Applicable duties and taxes.
 - .3 Delivery to the Place of the Work.
 - .4 Assembly contractors'/suppliers' only, expenses relating to the following:
 - .1 Handling at site, including unloading, uncrating, storage and hoisting.
 - .2 Protection from damage by elements or otherwise.
 - .3 Labour installation and finishing.
 - .4 Other expenses required to complete installation.
 - .5 Overhead and profit.

- .2 Include in the Bid Price any overhead and profit or related General Contractor costs.

- 4 **TESTING & LABORATORY SERVICES**
 - .1 Testing & Laboratory Services allowances shall include and provide payment for:
 - .1 Transportation costs to and from the Place of the Work,
 - .2 Personnel & equipment required to perform tests or inspections,
 - .3 Costs of shipping & handling samples to laboratory for testing,
 - .4 Applicable duties and taxes.

- 5 **ALLOWANCE AMOUNTS**
 - .1 The Total Cash Allowance to be included in the Stipulated Price is ~~\$545,000~~ **\$745,000** in Canadian funds.

 - .2 The Cash Allowance shall cover the following (in general):
 - .1 Finish Hardware – supply and installation of all finish hardware for wood and hollow metal doors. Supply of finish hardware for aluminum doors - installation by others. Supply of finish hardware for teacher's closet doors - installation by others.
 - .2 Pin mounted cast aluminum signage on exterior of building.
 - .3 Hydro Utility - supply and install of the primary terminations. Connection at supply point at street and pad mounted transformer. Utility service connection fees.
 - .1 Note: The Electrical Contractor shall be responsible for coordinating a servicing agreement and all associated work with the electrical company.
 - .4 Testing and Inspection.
 - .5 Security Alarm Systems -- Supply and install as per Division 26 Sections.
 - .6 A/V systems -- supply and install in gymnasium?
 - .7 Gas meter upgrades by Utility provider.
 - .8 Unexpended amounts of Cash Allowances may be reallocated to other work at the sole discretion of the Consultant and Owner.
 - .9 ***Handling or handling and disposal of contaminated soils.***

END OF SECTION

1 General

1.1 **SECTION INCLUDES**

- .1 Labour, Products, equipment and services necessary for the wood doors Work in accordance with the Contract Documents.

1.2 **REFERENCES**

- .1 ANSI A208.1, Particleboard.
- .2 Architectural Woodwork Standards (AWS) - Quality Standards for Architectural Woodwork.
- .3 CSA O112 Series, Wood Adhesives.
- .4 CAN4 S104-M, Standard Method for Fire Tests of Door Assemblies.
- .5 NFPA 80, Standard for Fire Doors and Other Opening Protectives.

1.3 **SUBMITTALS**

- .1 Shop drawings: Submit shop drawings of wood doors in accordance with the Conditions of the Contract indicating detail thicknesses, core construction, veneers, finish, door sizes, quantities, fastenings and finishes.
- .2 Samples: Submit the following samples in accordance with the Conditions of the Contract:
 - .1 Two minimum 300 x 300 mm door samples for each type of finish and cut-a-way corners showing construction and materials.

1.4 **QUALITY ASSURANCE**

- .1 Perform Work in accordance with requirements of AWS, Quality Standards for Architectural Woodwork, Premium Grade, except as indicated otherwise.
- .2 Regulatory Requirements For Fire Rated Doors:
 - .1 Fire Rating & Labeling: Fire rated doors shall be labelled and listed by an organization accredited by Standards Council of Canada in conformance with CAN4-S104 for ratings specified or indicated.
 - .2 Provide fire doors for stairwell enclosures that will limit maximum transmitted temperature to door surface on opposite fire side of door to less than 232°C above ambient temperature after 30 minutes of fire exposure.

1.5 **DELIVERY, STORAGE, AND HANDLING**

- .1 Deliver, store, and handle wood doors in accordance with the AWS Quality Standards amended as follows:
 - .1 Wrap wood doors individually in protective wrapping for shipment and Site storage.

- .2 Handle wood doors carefully to prevent damage; replace damaged doors.
- .3 Store doors flat on a dry, level surface. Ventilate and maintain recommended relative humidity before, during and after installation.

1.6 EXTENDED WARRANTY

- .1 Provide a Warranty certificate from the door manufacturer which binds the manufacturer to replace all doors found to have defects in factory workmanship or materials, or which warp more than 6mm out of plane, under normal use, for a minimum of five (5) years from the Date of Substantial Performance. Replacement doors shall bear same warranty from date of replacement.
- .2 "Replace" as used herein, does not include hanging, installation or field finishing. This work shall be performed by the Contractor for the warranty period stipulated in the General Conditions of the Contract. If doors were originally supplied factory finished, manufacturer must supply replacement doors with same finish.

2 Products

2.1 ACCEPTABLE MANUFACTURERS

- .1 Baillergeon.
- .2 Lambton Doors.

2.2 MATERIALS

- .1 General: All materials under Work of this Section, including but not limited to, adhesives are to have low VOC content limits.
- .2 Wood doors (solid core):
 - .1 5 ply wood door: As manufactured by Baillergeon Doors Inc. or Lambton Doors.
 - .2 Core: To ANSI A208.1, minimum density 513 kg/m³ minimum, sanded faces, of thickness to fill void. Extruded particle board cores with voids are not permitted.
 - .3 Rails:
 - .1 Top: 35 mm structural composite lumber.
 - .2 Bottom: 35 mm structural composite lumber.
 - .4 Stiles
 - .1 16 mm hardwood laminated to 19 mm structural composite lumber.
 - .2 Edge detail: AWMAC No.2.
 - .5 Crossbanding: Minimum 2.2 mm thick minimum wood based composite.
 - .6 Door facing: ~~Minimum 0.8 mm paint grade birch Veneer finished in accordance with Section 09 91 00~~ **Plastic laminate.**
- .3 Wood doors (fire rated):
 - .1 'Fire Door Series' by Baillergeon Doors Inc. or 'Fire Door' by Lambton Doors.
 - .2 Core: Fire rated mineral core. Density of 28-32 lbs per cubic foot.
 - .3 Internal blocking: AWS Option #3; Manufacturers' standard fire resistant blocking.

- .4 Top and Bottom Rails: 85 mm laminated strand lumber bonded with type 1 water-resistant adhesive as per ASTM-D1037 and ASTM-D198.
- .5 Stiles: 107 mm including 85 mm laminated strand lumber bonded with type 1 water-resistant adhesive as per ASTM-D1037 and ASTM-D198.
- .6 Crossbanding: Minimum 2.2 mm thick HDF composite.
- .7 Door facing: ~~Minimum 0.8 mm birch veneer finished in accordance with Section 09-91-00~~ **Plastic laminate.**

- .4 Edge finish: To match door facings.
- .5 Adhesive: CSA O112 Series, Type I; Waterproof.
- .6 Door frames: Metal door frames in accordance with Section 08 11 13.
- .7 Glass and glazing: In accordance with Section 08 80 00.
- .8 Door Hardware: To be supplied and installed under Cash Allowance.

2.3 **FABRICATION**

- .1 Fabricate doors to sizes indicated on drawings.
- .2 Fabricate doors square, true, and free from distortion waves, ridges or core ghost lines. Factory machine doors for finish hardware and flooring.
- .3 Fabricate doors using hot press construction technology. Bond stiles and rails to core using adhesive. Sand for uniform thickness. Laminate door facing and trim, to assembled core in hot press.
- .4 Cut and bevel stile edges as follows:
 - .1 Lock side: 3 mm in 50 mm.
 - .2 Hinge side: 1.5 mm in 50 mm.
- .5 Finish wood doors in factory and deliver to site ready for hanging.

2.4 **FIRE RATED DOORS**

- .1 Fabricate and label fire rated wood doors with plate label indicating fire protection rating as indicated on door schedule.

3 Execution

3.1 **EXAMINATION**

- .1 Verify condition and dimensions of previously installed Work upon which this Section depends. Report defects to Consultant. Commencement of Work means acceptance of existing conditions.

3.2 INSTALLATION

- .1 Install doors plumb, rigid, square, clear of floor finishes, and with correct rebate opening for door installation.
- .2 Conform to requirements of AWS Quality Standard, for wood door installation.

3.3 FIRE RATED DOORS

- .1 Install fire rated doors in accordance with the requirements of ULC and NFPA 80.

3.4 ADJUSTING AND CLEANING

- .1 Replace the following wood doors:
 - .1 Warped more than 3 mm, measured at any point on door, relative to perfectly flat surface.
 - .2 Core telegraphing visible at 1500 mm distance, under final Site lighting conditions.
- .2 Adjust doors for smooth and balanced door movement.

END OF SECTION

1 General

1.1 **SECTION INCLUDES**

- .1 Design, labour, Products, equipment, tools, and services necessary for glass and glazing Work in accordance with the Contract Documents.

1.2 **REFERENCES**

- .1 ASTM C1048, Standard Specification for Heat-Strengthened and Fully Tempered Flat Glass.
- .2 ASTM D2240, Test Method for Rubber Property - Durometer Hardness.
- .3 CAN/CGSB-12.1-M, Tempered or Laminated Safety Glass.
- .4 CAN/CGSB-12.8, Insulating Glass Units.
- .5 Glass Association of North America (GANA) Glazing Manual.
- .6 ULC CAN4 S104-M, Standard Method for Fire Tests of Door Assemblies.
- .7 ULC CAN4 S106-M, Standard Method for Fire Tests of Window and Glass Block Assemblies.

1.3 **DESIGN REQUIREMENTS**

- .1 Glass Design:
 - .1 Design glass using a probability of breakage of 8 lites per 1000 at the first application of design load.
 - .2 Perform stress analysis. Design units to accommodate live, dead, lateral, wind, seismic, handling, transportation, and erection loads.
 - .3 Perform a thermal stress analysis on each glass unit with Low-E coating and provide heat strengthening and/or tempered units as necessary to prevent thermal breakage.
 - .4 Perform a thermal stress analysis on each insulating thermal unit and provide heat strengthening and/or tempered units as necessary to prevent thermal breakage.
 - .5 Where required, design glazing units so as not to allow thermal stress fracture due to heat build-up behind insulating units.
- .2 Limit glass deflection to flexural limit of glass with full recovery of glazing materials.
- .3 Utilize inner light of multiple light sealed units for continuity of air and vapour seal.

1.4 SUBMITTALS

- .1 Shop drawings:
 - .1 Submit shop drawings in accordance with the Conditions of the Contract indicating as a minimum:
 - .1 Fabrication and erection of glazing elements indicating materials, thicknesses, finishes, connections, joints, method of anchorage, number of anchors, supports, reinforcement, details, and accessories.
 - .2 To sealant manufacturer for their review and approval of tensile bead contact/bite dimension and thickness.
 - .2 Samples:
 - .1 Submit following samples in accordance with the Conditions of the Contract.
 - .2 Submit one sample of each type of glass.
 - .1 300 x 300 mm of each type of insulating glass unit, complete with each different Low-E coating.
 - .2 300 x 300 mm of each colour of spandrel glass.
- .3 Certificates: Submit manufacturer's certification that glass and glazing materials are compatible.
- .3 Reports:
 - .1 Submit compatibility and adhesion test reports from sealant manufacturer indicating that glazing materials were tested for compatibility and adhesion with glazing sealants. Include sealant manufacturer's interpretation of test results relative to sealant performance and recommendations for primers and substrate preparation needed for adhesion.
 - .2 Compatibility test report from manufacturer of insulating glass edge sealant, indicating that glass edge sealants were tested for compatibility with other glazing materials including sealants, setting blocks, edge blocks and any other material that contacts or can affect the edge seal.
- .4 IGMA Compliance Audit: Submit in accordance with the Conditions of the Contract, a written certification of successful completion of a Compliance Audit within the last six months.

1.5 QUALITY ASSURANCE

- .1 Insulating glass unit fabricators shall be a certified member of the Insulating Glass Manufacturer's Alliance (IGMA). IGMA members must participate in the certification program and shall have successfully passed a Compliance Audit within the last six months.
- .2 Installers qualifications: Perform Work of this Section by a company that has a minimum of five years proven experience in the installation of glazing units of a similar size and nature.
- .3 Fire Protective Rated Glass: Each lite shall bear permanent, nonremovable label of ULC certifying it for use in tested and rated fire protective assemblies.

1.6 **SITE CONDITIONS**

- .1 Glaze with compounds, sealants, or tapes only when glazing surfaces are at temperatures over 4°C, and when positive that no moisture is accumulating on them from rain, mist, or condensation.
- .2 When temperature of glazing surfaces is below 4°C, obtain from Consultant approval of glazing methods and protective measures which will be used during glazing operations.

1.7 **EXTENDED WARRANTY**

- .1 In accordance with Section 08 51 13.

2 Products

2.1 **ACCEPTABLE MANUFACTURERS**

- .1 Glass manufacturers:
 - .1 AGC Flat Glass.
 - .2 Cardinal Glass Industries.
 - .3 Guardian Industries.
 - .4 PPG Industries Ltd.
 - .5 Viracon Inc.

2.2 **MATERIALS**

- .1 All materials under Work of this Section, including but not limited to, primers, coatings, sealers, sealants, adhesives and cleaners are to have low VOC content limits.
- .2 Tempered glass (**TG**): CAN/CGSB-12.1-M, Type 2, Class B, Category II, clear, minimum 6 mm thick.
- .3 Fire rated glass (**FRGL**): 20 min. to 90 min. fire rating tested to ULC CAN4 S104-M and ULC CAN4 S106-M, 5 mm thick or as otherwise noted on Door Schedule with appropriate labelling stating fire rating and approval, clear polished glass. Firelite by Nippon Electric Glass Company Ltd. or approved alternative.
- .4 Spandrel glass (**SGL**): ASTM C1048, Condition B, 6 mm thick heat strengthened or tempered glass, with water-based silicone emulsion coating applied to backside, 'Opaci-Coat 300' by ICD High Performance Coatings or approved alternative. Colour: To match PT-5, PT-6, PT-7, PT-8, PT-9, and PT-10 per room finish and colour schedule.
- .5 Insulating glass units: To CAN/CGSB-12.8-M and IGMA requirements utilizing approved non-metallic PVC or Fibreglass edge spacer in black. Dual seal with a PIB primary seal and silicone secondary seal.
- .6 Argon gas: 90% argon and 10% air mixture. Argon gas to be used to fill air space at all insulated glass units.

- .7 Low-E coating: High performance sputtered low-E coating. Provide insulating glass units with low-E coating edge deletion and low-E coating. Apply low-E coating to second surface unless otherwise indicated. 'EnergySelect 36' by AGC Flat Glass, 'Cardinal LoE-270' by Cardinal Glass Industries, 'SN 68' by Guardian Industries or 'Solarban 60' clear by PPG Industries Inc.
- .8 Glazing types:
 - .1 GL-1: Clear TG exterior lite with low-E coating, argon filled air space, clear TG interior lite. Standard throughout unless noted otherwise. 25 mm overall thickness.
 - .2 GL-2: 6 mm clear TG used at interior glass lites in non-rated doors and screens.
 - .3 GL-3: 5 mm FRGL used at interior fire-rated doors and screens.
- .9 Glazing and rebate primers, sealants, sealers, and cleaners: Compatible with each other. Type as recommended by glass manufacturer.
- .10 Glazing sealant: Silicone sealant as recommended by glazing manufacturer. Verify compatibility with insulating glass unit secondary sealant.
- .11 Heel & toe bead: Silicone sealant as recommended by glazing manufacturer.
- .12 Glazing gasket: 'Visionstrip' by Tremco Ltd., extruded composite glazing seal, size as recommended by manufacturer.
- .13 Glazing tape: 'Polyshim II' glazing tape EPDM shim.
- .14 Glazing tape (fire rated glass): Closed cell polyvinyl chloride (PVC) foam, coiled on release paper over adhesive on two sides, maximum water absorption by volume of 2 percent. Glass panels that exceed 1,393 sq. inches for 90-minute ratings must be glazed with fire-rated glazing tape supplied by manufacturer.
- .15 Glazing splines: EPDM or neoprene, extruded shape to suit glazing channel retaining slot, colour as selected.
- .16 Setting blocks (regular): EPDM, 80 - 90 Shore A durometer hardness to ASTM D2240, sized to suit glazing method, glass unit weight and area.
- .17 Edge blocks: EPDM, 60-70 Shore A Durometer hardness, sized with 3 mm clearance from glass edge and spanning glass thickness(es). Capable of withstanding weight of glass unit, self adhesive on face.
- .18 Silicone Sealant (fire rated glazing): One-part neutral curing silicone, medium modulus sealant, Type S; Grade NS; Class 25 with additional movement capability of 50 percent in both extension and compression (total 100 percent):
 - .1 Dow Corning 795 - Dow Corning Corp.
 - .2 Silglaze-II 2800 - General Electric Co.
 - .3 Spectrem 2 - Tremco Inc.
- .19 Glass presence markers: Easily removable, non-residue depositing.
- .20 Screws, bolts and fasteners: Type 304 stainless steel.

2.3 **FABRICATION**

- .1 Verify glazing dimensions on Site.
- .2 Clearly label each glass lite with maker's name and glass type. Ensure labels are easily removable, non-residue depositing type. Do not remove labels until after Work is accepted by Consultant.
- .3 Fabricate glazing not less than 3 mm smaller than rebate size in either dimension; allow for edge spacers, shims, and setting blocks as necessary.
- .4 Work shall have smooth finished surfaces free from distortion and defects detrimental to appearance and performance.
- .5 Carefully make and fit details. Take special care with exposed finished Work to produce a neat and correct appearance to the Consultant's acceptance.
- .6 Fabricate argon filled thermal units with air space filled minimum 90% with argon gas.

3 Execution

3.1 **EXAMINATION**

- .1 Verify condition and dimensions of previously installed Work upon which this Section depends. Report defects to Consultant. Commencement of Work means acceptance of existing conditions.
- .2 Verify that openings for glazing are correctly sized and within tolerance.
- .3 Verify that surfaces of glazing channels or recesses are clean, free of obstructions, and ready to receive glazing.
- .4 Laminated glass edges shall be completely covered by tape to protect against sealants and water if required by Manufacturer.

3.2 **PREPARATION**

- .1 Clean contact surfaces with solvent and wipe dry.
- .2 Seal porous glazing channels or recesses with substrate compatible primer or sealer.
- .3 Prime surfaces scheduled to receive sealant.

3.3 **INSTALLATION**

- .1 Provide glazing in accordance with IGMA recommendations. Provide continuous contact between glazing tapes and gasket to the glazing.
- .2 Install glazing to the Work of Sections 08 11 13, 08 14 16, 08 44 00, 08 51 13, **08 56 88** and 10 22 19.


- .3 Provide neat, straight sight lines. Trim excess glazing material flush with top of stops and fixed leg of frames.
- .4 Remove protective coatings, glazing stops, clean rebate and glass contact surfaces with solvent, wipe dry.
- .5 Apply primer/sealer to contact surfaces, prior to glazing.
- .6 Apply glazing tape as per manufacturer's instructions including recommended corner sealant.
- .7 Use setting blocks at 1/4 points and spacers to centre glass unit in frame.
- .8 Install glazing in accordance with reviewed shop drawings and manufacturer's written instructions. Install glazing with full contact and adhesion at perimeter. Maintain edge clearance recommended by glass manufacturer.
- .9 Apply a continuous heel bead of sealant around perimeter of inboard lite of the sealed unit and the metal framing.
- .10 Re-install glazing stops ensuring continuous contact and rattle-free installation. Do not distort glass. Trim tape protruding more than 2 mm above stop.
- .11 Install glazing gasket in accordance with manufacturer's recommendations.
- .12 Do not cut or abrade tempered, heat treated, or coated glass.
- .13 Install glass presence markers in two cross stripes extending from diagonal corners. Maintain markers until final clean-up.
- .14 Remove, dispose of, and replace broken, cut, abraded glass, and defective glass including but not limited to production dimples, 'tiger-stripping', chips, cracks, etc.
- .15 Exterior glass: Glaze units with gasket on exterior side and glazing tape on interior side. Seal gap between glazing and stop with sealant to depth equal to bite of frame. Apply cap head of sealant along void between stop and glazing, to uniform line, flush with sight line. Tool or wipe sealant surface smooth.
- .16 Interior glass: Glaze interior glass using glazing gasket glazing tape.
- .17 Fire rated glass:
 - .1 Place setting blocks located at quarter points of glass with edge block no more than 150 mm from corners.
 - .2 Cut glazing tape to length and set against permanent stops, flush with sight lines to fit openings exactly, with stretch allowance during installation.
 - .3 Glaze vertically into labeled fire-rated metal frames or partition walls with same fire rating as glass and push against tape for full contact at perimeter of pane or unit.
 - .4 Place glazing tape on free perimeter of glazing in same manner described above.
 - .5 Install removable stop and secure without displacement of tape.

.6 Install so that appropriate ULC markings remain permanently visible.

3.4 **CLEANING**

- .1 Immediately remove sealant and compound droppings from finished surfaces.
- .2 Remove labels, protective material, and glass presence markers from prefinished surfaces.
- .3 Clean glass surfaces with cleaning agents and methods in accordance with Manufacturer's written instructions.




END OF SECTION




**EXISTING SINGLE STOREY
KINDERGARTEN WING
RENOVATED TO CHILD
CARE AFTER NEW
ADDITION IS OCCUPIED**

Level 1 Floor Plan - Renovation
1: 125

Level 2 Floor Plan - Renovation
1: 125



No.	Revision	Date
12	Issued for Advertisement No. 6	04-25-2024
11	Issued for Tender & Permit	03-26-2024
10	Issued for Client Review	12-11-2023
9	Issued for Costing	10-02-2023
8	Issued for Coordination	08-16-2023
7	Issued for 90% CD	07-31-2023
6	Issued for 50% CD	07-04-2023
5	Issued for 100% DD	05-29-2023
4	Issued for 100% DD	03-24-2023
3	Issued for Client Review	02-14-2023
2	Issued for Review	02-06-2023
1	Issued for Client Review	01-17-2023



All dimensions to be checked and verified on the job by the Contractor. Any discrepancies are to be reported to the Consultant prior to action. Only the latest approved drawings to be used for construction in conformance with all applicable codes, by-laws and regulations. All drawings remain the property of the Consultant.
© Copyright Reserved.
These drawings and all that is represented herein are the exclusive property of Salter Pilon Architecture Inc. They may not be used or reproduced without written permission from Salter Pilon Architecture Inc.

salterpilon
architecture

151 Ferris Lane, Suite 400 Barrie, Ontario L4M 6C1
salterpilon.com t: 705.737.3530

Project Information
**J.J. O'Neill Catholic
Elementary School -
Addition / Renovation**
240 Marilyn Ave., Naparone, ON K7R 2L4

For
Algonquin and Lakeshore Catholic District
School Board

Drawing Title
**Ground & Second Floor
Plan - Renovation**







Date: 04-25-2024 Project No: 22026 Drawing No: A204
Drawn by: AB, JJ
Scale: As indicated

GLASS SPANDREL PANEL LEGEND:

1	GSP-1	2	GSP-2
3	GSP-3	4	GSP-4
5	GSP-5	6	GSP-6

GENERAL NOTES:

1. ALL EXISTING BRICK REMOVED FOR NEW OPENINGS IS TO BE CAREFULLY REMOVED AND STORED FOR FUTURE INFILLS AS INDICATED ON ELEVATION, FLOOR PLANS AND DEMOLITION PLANS.
 2. ALL EXISTING GREEN CONCRETE SURROUNDS TO BE PATCHED, CLEANED AND PAINTED AS PER COLOUR SCHEDULE.
 3. FOUNDATION WALL & FOOTINGS ARE PER THE STRUCTURAL DRAWINGS. REFER TO THE STRUCTURAL DRAWINGS FOR THE REQUIRED DEPTHS, SIZE, REINFORCING ETC.
 4. LOCATIONS OF ALL MECHANICAL AND ELECTRICAL ITEMS MUST BE COORDINATED WITH THE MECHANICAL AND ELECTRICAL DRAWINGS (E. RISERS, GRILLES, LIGHTS ETC.) ON SITE WITH ALL TRADES INVOLVED IN THE WORK.
- CJ - CONTROL JOINT LOCATIONS, REFER TO DETAIL 2/A203



No.	Revision	Date
1	Issued for SPA	07-17-2023
2	Issued for 90% CD	07-31-2023
3	Issued for Coordination	08-16-2023
4	Issued for Costing	10-05-2023
5	Issued for Client Review	10-11-2023
6	Issued for Tender & Permit	03-26-2024
7	Issued for Addendum No. 6	04-25-2024

Orientation	Seal

All dimensions to be checked and verified on the job by the Contractor. Any discrepancies are to be reported to the Consultant prior to action. Only the latest approved drawings to be used for construction in conformance with all applicable codes, by-laws and regulations. All drawings remain the property of the Consultant.

© Copyright Reserved.
These drawings and all that is represented herein are the exclusive property of Salter Pilon Architecture Inc. They may not be used or reproduced without written permission from Salter Pilon Architecture Inc.

salterpilon
architecture

151 Ferris Lane, Suite 400 Barrie, Ontario L4M 6C1
salterpilon.com t: 705.737.3530

Project Information

J.J. O'Neill Catholic Elementary School - Addition / Renovation
240 Marilyn Ave., Napawan, ON K7R 2L4

For Algonquin and Lakeshore Catholic District School Board

Drawing Title: **Building Elevations**

Date	04-25-2024	Project No	22026	Drawing No	A301
Drawn by	AB, JJ	Scale	As indicated		



- REFLECTED CEILING PLAN NOTES:**
- COORDINATE FULLY WITH MECHANICAL & ELECTRICAL DRAWINGS & SPECIFICATIONS TO ENSURE PROPER PLACEMENT OF ALL LIGHTS, GRILLES, EXHAUST FANS, DIFFUSERS ETC. RELATING TO THE REFLECTED CEILING PLAN LAYOUT.
 - ENCLOSE ALL EXPOSED STEEL STRUCTURE SUPPORTING FLOOR LOADS WITH (2) LAYERS OF 1/2" THICK GYPSUM BOARD OVER MECH. FRAMING ASSEMBLY TO PROVIDE A 1-HOUR FIRE RESISTANCE RATING. ALL DETAILS MUST COMPLY.
 - REFER TO ELECTRICAL DRAWINGS FOR LOCATION OF FUTURES FLUSH WITH GYPSUM WALL BOARDS CEILING AND REQUIRE CAREFUL FINISHING.
 - LOCATION OF PAINTED ACT CEILING TILES TO BE COORDINATED WITH OWNER & ARCHITECT ON SITE.
 - ALL EXPOSED STRUCTURE & DECK TO BE PAINTED AS PER COLOUR AND MATERIAL SCHEDULE.

- REFLECTED CEILING PLAN LEGEND:**
- Supply Air Diffuser as per Mech. DWG
 - Return Air Diffuser as per Mech. DWG
 - Exhaust Grille as per Mech. DWG
 - Radiant Cooling Panels as per Mech. DWG
 - Surface Mounted Luminaires as per Elec. DWG
 - Recessed Luminaires as per Elec. DWG
 - Recessed Light Fixture as per Elec. DWG
 - Wall Mounted Light Fixture as per Elec. DWG
 - 610 x 1200 Lay in Ceiling Tile
 - Acoustical Ceiling Panels Refer to Specification & Room Finish & Colour Schedule
 - ACP-1
 - ACP-2
 - ACP-3
 - ACP-4
 - ACP-5
 - ACP-6
 - ACP-7

No.	Revision	Date
11	Issued for Addendum No. 6	04-25-2024
10	Issued for Addendum No. 4	04-18-2024
9	Issued for Addendum No. 2	04-03-2024
8	Issued for Tender & Permit	03-29-2024
7	Issued for Client Review	12-11-2023
6	Issued for Coordination	10-09-2023
5	Issued for Coordination	08-16-2023
4	Issued for 50% CD	07-31-2023
3	Issued for 50% CD	07-24-2023
2	Issued for 100% DD	05-29-2023
1	Issued for SD	02-24-2023

No.	Revision	Date
11	Issued for Addendum No. 6	04-25-2024
10	Issued for Addendum No. 4	04-18-2024
9	Issued for Addendum No. 2	04-03-2024
8	Issued for Tender & Permit	03-29-2024
7	Issued for Client Review	12-11-2023
6	Issued for Coordination	10-09-2023
5	Issued for Coordination	08-16-2023
4	Issued for 50% CD	07-31-2023
3	Issued for 50% CD	07-24-2023
2	Issued for 100% DD	05-29-2023
1	Issued for SD	02-24-2023

All dimensions to be checked and verified on the job by the Contractor. Any discrepancies are to be reported to the Consultant prior to action. Only the latest approved drawings to be used for construction in conformance with all applicable codes, by-laws and regulations. All drawings remain the property of the Consultant.




© Copyright Reserved.
These drawings and all that is represented herein are the exclusive property of Salter Pilon Architecture Inc. They may not be used or reproduced without written permission from Salter Pilon Architecture Inc.

salterpilon
architecture

151 Ferris Lane, Suite 400 Barrie, Ontario L4M 6C1
salterpilon.com t: 705.737.3530

Project Information
J.J. O'Neill Catholic
Elementary School -
Addition / Renovation
240 Marilyn Ave., Naparone, ON K7R 2L4

For
Algonquin and Lakeshore Catholic District
School Board
Drawing Title
Reflected Ceiling Plan
Second Floor
Date: 04-25-2024 Project No: 22026 Drawing No: A702
Drawn by: AB, JJ Scale: As indicated



1
A702
Level 2 Reflected Ceiling Plan
1 : 100

Project Name:	ALCDSB J.J. O'Neill Catholic School	Date Issued:	April 23, 2024
Quasar Project #:	ED-22-764		

Distribution

Quasar Consulting Group.	Michael Hughes	Michael.hughes@quasarcg.com
Quasar Consulting Group	Carl Wagstaff	carl.wagstaff@quasarcg.com
Salter Pilon Architecture	James Jeffery	jjeffery@salterpilon.com

Addendum #:	M-3
Revision #:	0

This Addendum forms part of the Contract Specifications and Drawings, and modifies the Bidding Documents, with Amendments and Additions noted below. This Addendum shall be added to the front of the specifications as issued. Bidders shall acknowledge receipt of this Addendum in the space provided in the Bid Form and include in bid amount.

This addendum includes modifications to the drawings and specifications as summarized below. Unless otherwise noted, all drawings and/or specifications listed below are attached herewith.

Answers to Questions:

1. Mechanical Drawings show all zones exposed in the mech/water entry room. Spec section 21 13 00 references zone control riser module cabinets. Will any zones require to utilize these cabinets?
 - a. **No, cabinets are not required for zone control riser modules within Sprinkler Room.**
2. Drawing M-707 supervised valve schedule calls for an SV-3 to be a fire pump control valve? is there a requirement for a fire pump?
 - a. **No, a fire pump is not required. Supervised valve schedule has been revised as a part of this addendum.**
3. Is there an existing sprinkler system in the building? The drawings are unclear regarding this. Are there any pictures/ drawings of any modifications that need to happen to any existing sprinkler systems?
 - a. **No, there is no existing sprinkler system within the building.**
4. Spec section 21 13 00 references window sprinklers. Are there any requirements for a window sprinkler system?
 - a. **No, there is no requirement for window sprinklers.**
5. Spec section 21 13 00 references preaction zones and dry pipe zones. Are there any unheated or water sensitive rooms that require either?
 - a. **No, there is no requirement for preaction systems.**
6. Spec section 21 13 00 references P.I.V.'s, drawings do not indicate any locations. Is there a requirement for a P.I.V.?
 - a. **No, there is no requirement for a P.I.V.**
7. Spec section 21 13 00 references a 6" engraved laminate tags for the loss of pressure switch and flow alarm switches. Please be advised that a 6" tag will not fit onto a ps 10/ps 120 switch. Are these indeed required?
 - a. **Laminated tags are required. Size of tags are to be suitable for devices.**
8. Spec section 21 13 00 references alarm check valves and excess pressure pumps. Can riser manifolds be used instead? The use of water motor gongs would be omitted if riser manifolds are used. The use of Excess pressure pumps would be omitted if riser manifolds are used. Will this be accepted?
 - a. **This is acceptable.**
9. The use of low pressure switches would be omitted if riser manifolds are used. Will this be accepted?
 - a. **This is acceptable.**


Changes to Drawings:

1. **M-250– PLUMBING NEW WORK – UNDERGROUND**
 - a. Revised elevator sump pit to be pre-fabricate sump pit.
2. **M-707– FIRE PROTECTION SCHEMATIC**
 - a. Revised Supervised Valve Schedule as shown.
3. **M-803– MECHANICAL TYPICAL DETAILS IV**
 - a. Revised detail of Elevator Sump Pump & Pit Sanitary Discharge to show pre-fabricated sump pit.
4. **M-901– MECHANICAL SCHEDULES II**
 - a. Revised Schedule of Rooftop Units to account for revised model numbers.


Quasar Consulting Group

Michael Hughes

Team Lead, P. Eng.



No.	Revision	Date
14	ISSUED FOR ADDENDUM M-3	2024-04-23
13	ISSUED FOR ADDENDUM M-2	2024-04-12
12	ISSUED FOR ADDENDUM M-1	2024-04-02
11	ISSUED FOR TENDER & PERMIT	2024-03-26
10	ISSUED FOR TENDER REVIEW	2023-03-15
9	ISSUED FOR COORDINATION REVIEW	2023-02-28
8	ISSUED FOR SITE PLAN APPLICATION	2023-11-21
7	ISSUED FOR COSTING	2023-10-03
6	ISSUED FOR 90% CD	2023-08-03
5	ISSUED FOR 80% CD	2023-07-31
4	ISSUED FOR 50% CD	2023-07-05
3	ISSUED FOR COORDINATION	2023-06-29
2	ISSUED FOR 100% DD	2023-05-30
1	ISSUED FOR SITE PLAN APPLICATION	2023-05-03



All dimensions to be checked and verified on the job by the Contractor. Any discrepancies are to be reported to the Consultant prior to action. Only the latest approved drawings to be used for construction in conformance with all applicable codes, by-laws and regulations. All drawings remain the property of the Consultant.

© Copyright Reserved. These drawings and all that is represented herein are the exclusive property of Quasar Consulting Group Inc. They may not be used or reproduced without written permission from Quasar Consulting Group Inc.



250 ROWNTREE DAIRY RD, WOODBRIDGE, ON
 TEL: 905-507-0800
 WEB: WWW.QUASARGROUP.COM
 QUASAR PROJECT No.: ED-22-069


Project Information
J.J. O'Neill Catholic Elementary School - Addition / Renovation
 240 Marilyn Ave., Napanee, Ontario K7R 2L4
 For: Algonquin and Lakeshore Catholic District School Board

Drawing Title
PLUMBING NEW WORK- UNDERGROUND

Date	MAY 2023	Project No	22-206M-250	Drawing No	
Drawn by	B.O.				
Scale	1:100				

C:\Users\mbalwco\Documents\2024-CSDCEO - St Viateur Central_lambarucci.rvt 2022-11-22 3:49:23 PM


C:\Users\stibari\OneDrive\Documents\2024 - CSDCEC - St. Valerie Central - Jbaridukci.rvt
2022-11-22 3:49:23 PM



SUPERVISED VALVE SCHEDULE		
VALVE NO.	VALVE LOCATION	FUNCTION
SV-1	INCOMING MECHANICAL & SPRINKLER ROOM	INCOMING FIRE WATER MAIN ISOLATION
SV-2	INCOMING MECHANICAL & SPRINKLER ROOM	SPRINKLER DOUBLE CHECK ISOLATION
SV-3	INCOMING MECHANICAL & SPRINKLER ROOM	SPRINKLER DOUBLE CHECK ISOLATION
SV-4	INCOMING MECHANICAL & SPRINKLER ROOM	L1 CONTROL VALVE (WET ZONE 1)
SV-5	INCOMING MECHANICAL & SPRINKLER ROOM	L1 CONTROL VALVE (WET ZONE 2)
SV-6	INCOMING MECHANICAL & SPRINKLER ROOM	L2 CONTROL VALVE (WET ZONE 1)
SV-7	INCOMING MECHANICAL & SPRINKLER ROOM	L2 CONTROL VALVE (WET ZONE 2)

- NOTES:
- VERTICAL BACKFLOW PREVENTION ASSEMBLY INSTALLATION ONLY PERMITTED PER LISTING.
 - PIPE UPSTREAM OF BACKFLOW PREVENTION SHALL BE DUCTILE IRON.
 - CONTRACTOR SHALL PROVIDE PROVISIONS FOR TESTING THE DOUBLE CHECK VALVE ASSEMBLY TO ACCOMMODATE THE LARGEST SYSTEM DEMAND.
 - FIRE DEPARTMENT DRY PIPE TO EXTERIOR SHALL BE GALVANIZED. VALVES AND GAUGES SHALL BE INSTALLED WITHIN ACCESSIBLE HEIGHT (MAX 1.8M AFF).

No.	Revision	Date
11	ISSUED FOR TENDER & PERMIT	2024-03-26
10	ISSUED FOR TENDER REVIEW	2023-03-15
9	ISSUED FOR COORDINATION REVIEW	2023-02-28
8	ISSUED FOR SITE PLAN APPLICATION	2023-11-21
7	ISSUED FOR COSTING	2023-10-03
6	ISSUED FOR 100% CD	2023-08-03
5	ISSUED FOR 80% CD	2023-07-31
4	ISSUED FOR 50% CD	2023-07-26
3	ISSUED FOR COORDINATION	2023-06-29
2	ISSUED FOR 100% DD	2023-05-30
1	ISSUED FOR SITE PLAN APPLICATION	2023-05-03



All dimensions to be checked and verified on the job by the Contractor. Any discrepancies are to be reported to the Consultant prior to action. Only the latest approved drawings to be used for construction in compliance with all applicable codes, by-laws and regulations. All drawings remain the property of the Consultant.

© Copyright Reserved.
These drawings and all that is represented herein are the exclusive property of Satter Pipe Architecture Inc.
They may not be used or reproduced without written permission from Satter Pipe Architecture Inc.



250 ROWINTREE DAIRY RD, WOODBRIDGE, ON
TEL: 905-507-0800
WEB: WWW.QUASARC.G.COM


QUASAR PROJECT No.: ED-22-069

Project Information
J.J. O'Neill Catholic
Elementary School -
Addition / Renovation
240 Marilyn Ave., Napanee, Ontario K7R 2L4


For
Algonquin and Lakeshore Catholic District
School Board

Drawing Title
**FIRE PROTECTION
SCHEMATIC**


Date	Project No	Drawing No
MAY 2023		
Drawn by B.O	22-206	M-707
Scale N.T.S.		




22 13 00.01 DWV ROOF PENETRATION & VENT CAP COVER




21 13 00.02 SPRINKLER ZONE CONTROL VALVE





22 30 00.04 ELEVATOR SUMP PUMP & PIT SANITARY DISCHARGE




22 11 00.01 REDUCED PRESSURE ZONE ASSEMBLY




21 13 00.05 UNDERGROUND FIRE MAIN




22 11 00.03 MUNICIPAL/PRIVATE WATER METER



21 13 00.01 FIRE DEPARTMENT CONNECTION




22 13 00.02 SANITARY & STORM WATER CLEANOUTS



21 13 00.02 SANITARY & STORM WATER CLEANOUTS

No.	Revision	Date
11	ISSUED FOR TENDER & PERMIT	2024-03-26
10	ISSUED FOR TENDER REVIEW	2023-03-15
9	ISSUED FOR COORDINATION REVIEW	2023-02-28
8	ISSUED FOR SITE PLAN APPLICATION	2023-11-21
7	ISSUED FOR COSTING	2023-10-03
6	ISSUED FOR 90%CD	2023-08-03
5	ISSUED FOR 80%CD	2023-07-31
4	ISSUED FOR 50%CD	2023-07-26
3	ISSUED FOR COORDINATION	2023-06-29
2	ISSUED FOR 100% CD	2023-05-30
1	ISSUED FOR SITE PLAN APPLICATION	2023-05-03



All dimensions to be checked and verified on the job by the Contractor. Any discrepancies are to be reported to the Consultant prior to action. Only the latest approved drawings to be used for construction in conformance with all applicable codes, by-laws and regulations. All drawings remain the property of the Consultant.

© Copyright Reserved. These drawings and all that is represented herein are the exclusive property of Quasar Consulting Inc. They may not be used or reproduced without written permission from Quasar Consulting Inc.

QUASAR CONSULTING GROUP

250 ROWNTREE DAIRY RD, WOODBRIDGE, ON
 TEL: 905-507-0800
 WEB: WWW.QUASARCG.COM

QUASAR PROJECT No.: ED-22-069

Project Information

J.J. O'Neill Catholic Elementary School - Addition / Renovation
 240 Marilyn Ave., Napanee, Ontario K7R 2L4

For
 Algonquin and Lakeshore Catholic District School Board

Drawing Title
MECHANICAL TYPICAL DETAILS IV

Date: MAY 2023
 Drawn by: B.O.
 Scale: N.T.S.

Project No: 22-206
 Drawing No: M-803

ROOFTOP UNITS table with columns: UNIT TAG, MANUFACTURER, MODEL, LOCATION, SERVICE, SUPPLY FAN (AIRFLOW, E.S.P., OUTDOOR), EXHAUST FAN (AIRFLOW, E.S.P.), ASSOCIATED ENERGY RECOVERY WHEEL, COOLING (CAPACITY, PERFORMANCE), HEATING (CAPACITY, PERFORMANCE), FILTER, EFFICIENCY, ELECTRICAL, REMARKS.

NOTES: 1. 600MM HIGH ROOF CURB. 2. HEATING PERFORMANCE BASED ON ENTERING GLYCOL TEMPERATURE OF 7°C AND LEAVING GLYCOL TEMPERATURE OF 48°C. 3. ROOFTOP UNIT SHALL HAVE SINGLE POINT POWER FEED... 4. EACH UNIT SHALL BE IN CONFORMANCE WITH ASHRAE 90.1-2010 EFFICIENCY.

ENERGY RECOVERY WHEELS table with columns: UNIT TAG, MANUFACTURER, MODEL, SERVICE, HEAT WHEEL SUMMER PERFORMANCE, HEAT WHEEL WINTER PERFORMANCE, REMARKS.

NOTES: 1. ENERGY RECOVERY WHEEL SHALL BE PROVIDED WITH VFD FOR MODULATION OF WHEEL.

MISCELLANEOUS FANS table with columns: UNIT TAG, MANUFACTURER, MODEL, LOCATION, SERVICE, AIRFLOW, S.P. (Pa), NOMINAL RPM, ELECTRICAL, WEIGHT (KG), SONES, REMARKS.

NOTES: 1. VIBRATION ISOLATION HANGERS. 2. GRAVITY BACKDRIFT DAMPER. 3. 600MM ROOF CURB. 4. REVERSE-ACTING THERMOSTAT. 5. PROVIDE WITH REVERSOMATIC MODEL DAS-200 AMP SENSOR FAN CONTROL AND LT-300-45 LINT TRAP.

SPLIT SYSTEM AIR CONDITIONING UNITS table with columns: SYSTEM TAG, MANUFACTURER, MODEL NO., LOCATION, COOLING CAPACITY (KW), AIRFLOW - HI/LOW, WEIGHT (KG), ELECTRICAL, SYSTEM TAG, LOCATION, MODEL NO., AIRFLOW RATE (L/S), WEIGHT (KG), ELECTRICAL.

NOTES: 1. REFRIGERANT SHALL BE R410A. 2. INDOOR UNIT SHALL COME WITH INTEGRAL DRAIN PUMP. 3. PROVIDE A LOW AMBIENT TEMPERATURE KIT. 4. PROVIDE ROOF MOUNTING STAND EQUAL TO ECO FOOT 'ECO FRAME' TO RAISE CONDENSING UNITS MINIMUM 450MM ABOVE ROOF.

VARIABLE AIR VOLUME BOXES table with columns: TAG, MANUFACTURER, MODEL, QUANTITY, VAV SIZE, INLET SIZE (MM), MIN. AIRFLOW (L/S), MAX. AIRFLOW (L/S), DISCHARGE NC, RADIATED NC, ATTENUATOR LENGTH (MM), AIR PRESSURE DROP (Pa), REMARKS.

NOTES: 1. DDC CONTROLLER/ACTUATOR SHALL BE SUPPLIED BY CONTROLS MANUFACTURER AND INSTALLED BY VAV BOX MANUFACTURER.

EXPANSION TANK SCHEDULE table with columns: UNIT TAG, MANUFACTURER, MODEL, SERVICE, TANK VOLUME (L), ACCEPTANCE VOLUME (L), MAX OPERATING PRESSURE (KPa), RELIEF PRESSURE (KPa), MAX OPERATING TEMPERATURE (°C), WEIGHT (KG), REMARKS.

GRILLES, REGISTERS AND DIFFUSERS SCHEDULE table with columns: TAG, MANUFACTURER, MODEL, TYPE, SIZE, FINISH, MAX NC, REMARKS.


NOTES: 1. REFER TO SPECIFICATIONS AND DETAILS FOR MORE INFORMATION.

RADIANT FLOOR HEATING CAPACITY OUTPUT SCHEDULE (Klimatrol Environmental Systems)

Radiant floor heating capacity output schedule table with columns: TAG, ZONES, Manufacturer Supplier, TOTAL OUTPUT, FLOW, EWT, LWT, FLUID PRESSURE DROP, Pipe Spacing, AREA, OUTPUT PER AREA, MAX SURFACE TEMPERATURE, COMMENTS.

Notes for Radiant Floor Heating: - Klimatrol Environmental Systems Ltd. (905) 454-1742 is the basis of design. - Supply Klimatrol Hydronic System consisting of - 'ANURAV PANELS' c/w (1/2" RaupeX PEKa, Pumps, Manifolds, Cabinets, BACnet Controllers, Mixing Valves, Actuator, Circuit and Transformers, Pipe Ties, Bend Guides,).








Revision table with columns: No., Revision, Date.



All dimensions to be checked and verified on the job by the Contractor. Any discrepancies are to be reported to the Consultant prior to action. Only the latest approved drawings to be used for construction in compliance with all applicable codes, by-laws and regulations. All drawings remain the property of the Consultant.

QUASAR CONSULTING GROUP logo and contact information: 250 ROWNTREE DAIRY RD, WOODBRIDGE, ON TEL: 905-507-0800 WWW.QUASARCG.COM


Project information: Project Name: J.J. O'Neill Catholic Elementary School - Addition / Renovation, Location: 240 Marilyn Ave., Napawan, Ontario K7R 2L4, Drawing Title: MECHANICAL SCHEDULES II, Date: MAY 2023, Project No: 22-206, Drawing No: M-901, Scale: N.T.S.



All drawings and related documents are the copyright of the Architect and must be returned upon request. Reproductions of drawings and related documents in part or whole is forbidden without the Architect's written permission.

CONTRACTOR SHALL CHECK AND VERIFY ALL DIMENSIONS ON THE JOB.

THESE DRAWINGS SHALL NOT BE USED FOR CONSTRUCTION PURPOSES UNLESS SIGNED BY THE ARCHITECT.





JACKSON YPES ASSOCIATES

ARCHITECTS ENGINEERS


WILLOWDALE ONTARIO

J.J. O'NEILL SCHOOL
JAPANESE/RICHMOND, ONTARIO
FRONTENAC-LENNOX
AND ADDINGTON COUNTY
ROMAN CATHOLIC
SEPARATE SCHOOL BOARD

ROOM ELEVATIONS SHOWING FITMENTS.		JOB No. 8218
DRAWN D.W.	CHECKED G.E.R.	DWG#
SCALE 1:50 AND AS SHOWN.	DATE FEB. 7 '82	10



MECHANICAL ROOM #1




MECHANICAL ROOM #2

THIS CONTRACTOR SHALL CHECK AND VERIFY THESE DRAWINGS WITH THE ARCHITECTURAL DRAWINGS AND REPORT ANY INCONSISTENCIES TO THE ARCHITECT BEFORE PROCEEDING WITH THE WORK.

All drawings and related documents are the copyright of the Architect and must be returned upon request. Reproductions of drawings and related documents in part or whole is forbidden without the Architect's written permission.


CONTRACTOR SHALL CHECK AND VERIFY ALL DIMENSIONS ON THE JOB.




JACKSON YPES ASSOCIATES
ARCHITECTS
ENGINEERS
WILLOWDALE ONTARIO

J.J. O'NEILL SCHOOL
NAPANEE/RICHMOND
FRONTENAC LENNOX
AND ADDINGTON COUNTY
ROMAN CATHOLIC
SEPARATE SCHOOL BRD.

FLOOR PLAN PUMP & DRAINAGE		JOB NO. 8218
DRAWN A.V.P.	CHECKED K.G.	DWG. NO. P2
SCALE 1:100	DATE 7 FEB 83	







WEST ARCH BATTEN - CCTS 2L-7, 9, 11
EAST ARCH BATTEN - CCTS 2L-8, 10, 12
OFF-STAGE BATTEN - CCTS 2L-14, 16, 18
HOUSE LIGHTS - CCTS 2L-20, 22-1, 22-2
HOUSE LIGHTS - CCTS 2L-24, 27-1, 21
KEY-OPERATED SW. (THIS SWITCH ONLY)
FOR LUNCHROOM 'NIGHTLIGHTS'

STAGE DIMMING STATION
N.T.S.

PART PLAN - STAGE
N.T.S.




NOTES

- ELECTRICAL HTR. IN ELECT. R. TO BE 1500W, 208V, 1#, 60H. BASEBOARD TYPE. FPE#H27. C/W THERMOSTAT TYPE# HDT-14 (1219mm Long)
- PROVIDE 10-40mm CONDUIT & FOR 'FUTURE' CONNECTION TO RELOCATABLES AS FOLLOWS:
6-40mm EMT BETWEEN INTERFACE & MAIN SWITCHGEAR DIST. PNL.
1-40mm EMT BETWEEN INTERFACE & LPIL (CORRIDOR LTG.)
1-40mm EMT BETWEEN INTERFACE & P/A RACK
1-40mm EMT BETWEEN INTERFACE & FIRE ALARM CONTROL PANEL
1 SPARE TO RUN BETWEEN INTERFACE & ELECT. RM.
* PROVIDE JUNCTION/PULL BOX AT TERMINAL END OF CONDUIT (INTERFACE)

THIS CONTRACTOR SHALL CHECK AND VERIFY THESE DRAWINGS WITH THE ARCHITECTURAL DRAWINGS AND REPORT ANY INCONSISTENCIES TO THE ARCHITECT BEFORE PROCEEDING WITH THE WORK.

All drawings and related documents are the copyright of the Architect and must be retained upon request. Reproduction of drawings and related documents in part or whole is forbidden without the Architect's written permission.


CONTRACTOR SHALL CHECK AND VERIFY ALL DIMENSIONS ON THE JOB.




JACKSON YPES ASSOCIATES
ARCHITECTS
ENGINEERS
WILLOWDALE ONTARIO


J. J. O'NEILL SCHOOL
NAPANEE/RICHMOND
FRONTENAC LENOX
AND ADDINGTON COUNTY
ROMAN CATHOLIC
SEPARATE SCHOOL BRD.

LIGHTING & POWER LAYOUT		JOB No. 8218
DRAWN J. ROBERT MARSHALL	CHECKED N.C.	DWG NO. E3
SCALE 1:100	DATE 7 FEB 83	







H O T W A T E R H E A T I N G F L O W D I A G R A M N. T. S.




S U P P L Y A I R C O N T R O L S Y S T E M F O R S / A U N I T N ° 2 A N D S / A U N I T N ° 3




A I R C O M P R E S S O R A N D D R Y E R S Y S T E M




R O O M T E M P E R A T U R E C O N T R O L S Y S T E M




T Y P I C A L W A L L F I N P I P I N G D I A G R A M N. T. S.



D E T A I L O F F I R E D A M P E R T H R U R A T E D W A L L N. T. S.




D E T A I L O F R O O F C U R B F O R C H I M N E Y N. T. S.




D E T A I L O F C E I L I N G G R I L L O R D I F F U S E R N. T. S.

L E G E N D

SYMBOL	DESCRIPTION
	SUPPLY AIR DIFFUSER
	RETURN AIR OR EXHAUST REGISTER
	SUPPLY AIR DUCT
	RETURN AIR DUCT
	BALANCING DAMPER
	FIRE STOP FLAP
	FIRE DAMPER
	HEATING SUPPLY PIPING
	HEATING RETURN PIPING
	FORCE FLOW HEATING
	GATE VALVE
	STRAINER
	3-WAY VALVE
	SUPPLY AIR
	RETURN AIR
	THERMOMETER
	THERMOSTAT
	ACOUSTIC LINING
	PIPE DROP
	PIPE RISE
	MOTORIZED DAMPER





S E C T I O N (1) S C A L E 1 : 5 0



S E C T I O N (2) S C A L E 1 : 5 0

THE CONTRACTOR SHALL CHECK AND VERIFY THE ACCURACY OF ALL DIMENSIONS AND CONDITIONS OF THE WORK AND SHALL BE RESPONSIBLE FOR THE CORRECTION OF ANY DEFECTS OR OMISSIONS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE PROTECTION OF ALL EXISTING UTILITIES AND STRUCTURES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE PROTECTION OF ALL EXISTING UTILITIES AND STRUCTURES.



JACKSON YPES ASSOCIATES
ARCHITECTS ENGINEERS
WILLOWDALE ONTARIO

J. J. O'NEILL SCHOOL
NAPANEE/RICHMOND
FRONTENAC LENNOX
AND ADDINGTON COUNTY
ROMAN CATHOLIC
SEPARATE SCHOOL BRD.

DETAILS AND CONTROL DIAGRAMS 8218		JOB No.
DRAWN	CHECKED	DWS. No.
A.V.P.	K.G.	M2
SCALE	DATE	
N.T.S.	7 FEB 83	

PANEL SCHEDULE													
PANEL NO	MTG.	MAIN BREAKER	SINGLE POLE			TWO POLE			THREE POLE			SPACES	TOTAL
			15A	20A	OTHER	15A	20A	OTHER	15A	20A	OTHER		
LP-1L	S	225A	32	1	—	1	1	1 @ 30A	1	—	—	—	42
LP-2L	F	225A	36	4	1 @ 30A	—	—	—	3	—	—	—	42
LP-3L	F	225A	40	—	—	—	—	1 @ 30A	—	—	—	—	42

FIRE ALARM ZONE SCHEDULE	
ZONE	LOCATION
1	SOUTH WING CLASSROOMS, ELECTRICAL RM., JANITORS' OFFICE & STORAGE RMs.
2	GENERAL PURPOSE ROOM, CHANGE ROOMS, STORAGE, STAGE & KITCHEN
3	LUNCH ROOM, OFFICES, STAFF RM. & LIBRARY
4	MECHANICAL ROOM #1
5	MECHANICAL ROOM #2
6	RELOCATABLE CLASSROOMS
7	SPACE
8	SPACE
9	SPACE
10	SPACE
11	SPACE
12	SPACE


FIRE ALARM MOTOR SHUTDOWN

① PROVIDE DOUBLE VOLTAGE RELAYS FOR FIRE ALARM SHUTDOWN FOR:
 AH-1,-2,-3; RF-2,-3; PP-1,-2,-3; DR-1,-2;
 FA-8 & FA-9, FA-12 & FA-17

THIS CONTRACTOR SHALL CHECK AND VERIFY THESE DRAWINGS WITH THE ARCHITECTURAL DRAWINGS AND REPORT ANY INCONSISTENCIES TO THE ARCHITECT BEFORE PROCEEDING WITH THE WORK.

All drawings and related documents are the copyright of the Architect and must be returned upon request. Reproductions of drawings and related documents in part or whole is forbidden without the Architect's written permission.

CONTRACTOR SHALL CHECK AND VERIFY ALL DIMENSIONS ON THE JOB.




JACKSON YPES & ASSOCIATES
ARCHITECTS
ENGINEERS

WILLOWDALE ONTARIO

J. J. O'NEILL SCHOOL
 NAPANEE/RICHMOND
 FRONTENAC LENNOX
 AND ADDINGTON COUNTY
 ROMAN CATHOLIC
 SEPARATE SCHOOL BRD.

SINGLE LINE RISER DIAGRAM & LEGEND	JOB NO. 8218
DRAWN J. R. M.	CHECKED M. C.
SCALE 1:100	DATE 7 FEB 83



ELECTRICAL POWER DISTRIBUTION RISER DIAGRAM